



TECHNICAL DATA SHEET  
v042015

# XTC 5W40

## DESCRIPTION

High performance synthetic oil for petrol and diesel engines dated from 2000 and later. It is suitable for turbo-charged or not, multivalve and diesel direct injection engines.

## APPLICATION

Bardahl XTC 5w40 can be used all year long and in the most difficult operating conditions. It is compatible with catalytic converters.

## SPECIFICATIONS

This product offers the following performance level:

ACEA	A3 B4 -12
API	SN / CF
VW	502.00 / 505.00
MB	229.3 / 226.5
Porsche	A40
BMW	Longlife-01
GM	LL-B-025
PSA	B71 2296
Renault	RN0700 / RN0710
Fiat	9.55535-M2

## PROPERTIES

- ✓ Offers a stable viscosity.
- ✓ Provides an excellent resistance against shearing.
- ✓ Makes cold starting easier.
- ✓ Offers a good resistance against oxidation.

### SADAPS BARD AHL ADDITIVES & LUBRICANTS

ZI Tournai Ouest - 3, Rue du Mont des Carliers - B-7522 TOURNAI  
Tél. : +32 69 590 360 - Fax : +32 69 590 361 - [www.bardahlfrance.com](http://www.bardahlfrance.com)



## XTC 5W40

### TECHNICAL DATA

Density at 15°C	Kg/l	0,853
Viscosity at -35°C	mPa.s	5410
Viscosity at 40°C	mm <sup>2</sup> /s	88,40
Viscosity at 100°C	mm <sup>2</sup> /s	14,60
Viscosity Index		173
Flash point COC, °C	°C	223
Pour point, °C	°C	-42
TBN alcalinity	mgKOH/g	10,5
Sulphated ash contents	%	1,33

### RECOMMENDATIONS

Handling: any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

### REFERENCES & AVAILABILITIES

36160	6 x 400 ML
36161	12 x 1 L
36163	3 x 5 L
36168	20 L
36164	60 L
36167	205 L

#### SADAPS BARD AHL ADDITIVES & LUBRICANTS

ZI Tournai Ouest - 3, Rue du Mont des Carliers - B-7522 TOURNAI  
Tél. : +32 69 590 360 - Fax : +32 69 590 361 - [www.bardahlfrance.com](http://www.bardahlfrance.com)