



# XTEC 5W30 C3

## DESCRIPTION

Fuel economy synthetic engine oil formulated from last generation additives and specially developed for vehicles equipped with a particle filter (DPF), conforming to the EURO IV et EURO V norms.

## APPLICATION

Bardahl XTEC 5w30 C3 has been developed according to the Mid S.A.P.S/low HTHS technology. It is a very high performance and low viscosity lubricant, formulated to reduce fuel consumption and exhaust emissions. Particularly recommended for last generation BMW, MERCEDES, PORSCHE, VW, AUDI, SEAT, SKODA, petrol or diesel engines, requiring an ACEA C3 engine oil performance level.

## SPECIFICATIONS

This product offers the following performance level:

|               |               |
|---------------|---------------|
| ACEA          | C3-12         |
| VW            | 504.00/507.00 |
| MERCEDES-BENZ | MB 229.51     |
| PORSCHE       | C30           |
| BMW           | Longlife-04   |

## PROPERTIES

- ✓ Avoids fuel overconsumption.
- ✓ Compatible with modern catalytic converters.
- ✓ Extends the drain intervals.
- ✓ Offers excellent dispersion and detergency properties.
- ✓ Makes cold starting easier.
- ✓ Offers an excellent resistance against shearing.
- ✓ Provides a high protection against corrosion, wear and the formation of foam.

### SADAPS BARD AHL ADDITIVES & LUBRICANTS



## XTEC 5W30 C3

### TECHNICAL DATA

|                        |                    |       |
|------------------------|--------------------|-------|
| Density at 15 °C       | Kg/l               | 0,851 |
| Viscosity at -35 °C    | mPa.s              | 5950  |
| Viscosity at 40 °C     | mm <sup>2</sup> /s | 69,2  |
| Viscosity at 100 °C    | mm <sup>2</sup> /s | 12,00 |
| Viscosity Index        |                    | 171   |
| Flash point COC, °C    | °C                 | 230   |
| Pour point, °C         | °C                 | -42   |
| TBN alcalinity         | mgKOH/g            | 6,7   |
| Sulphated ash contents | %                  | 0,67  |

### RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

### REFERENCES & AVAILABILITIES

|       |            |
|-------|------------|
| 36300 | 6 x 400 ML |
| 36301 | 12 x 1 L   |
| 36303 | 3 x 5 L    |
| 36308 | 20 L       |
| 36304 | 60 L       |
| 36309 | 205 L      |

### SADAPS BARDAHL ADDITIVES & LUBRICANTS

ZI Tournai Ouest - 3, Rue du Mont des Carliers - B-7522 TOURNAI  
Tél. : +32 69 590 360 - Fax : +32 69 590 361 - [www.bardahlfrance.com](http://www.bardahlfrance.com)



TECHNICAL DATA SHEET  
v042015