



TECHNICAL DATA SHEET
v062015

XTG 80W90

DESCRIPTION

Mineral extreme pressure gear oil formulated for the lubrication of heavy loaded mechanical transmissions: gearboxes, transaxles and differentials.

APPLICATION

Bardahl XTG 80w90 is particularly suitable for heavy loaded hypoid differentials.

SPECIFICATIONS

This product offers the following performance level:

API	GL5
-----	-----

PROPERTIES

- ✓ Offers very strong extreme pressure (EP) properties.
- ✓ Has a low pour point.
- ✓ Provides a high resistance against corrosion and oxidation.
- ✓ Provides anti-wear and antifoam properties.

SADAPS BARDAHL ADDITIVES & LUBRICANTS

ZI Tournai Ouest - 3, Rue du Mont des Carliers - B-7522 TOURNAI
Tél. : +32 69 590 360 - Fax : +32 69 590 361 - www.bardahlfrance.com



XTG 80W90

TECHNICAL DATA

Density at 15 °C	Kg/l	0,893
Viscosity at 40 °C	mm ² /s	150,5
Viscosity at 100 °C	mm ² /s	15,2
Viscosity index		102
Flash point COC, °C	°C	214
Pour point, °C	°C	-27

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36271	12 x 1 L
36273	3 x 5 L
36278	20 L
36274	60 L
36277	205 L

SADAPS BARDAHL ADDITIVES & LUBRICANTS