



TECHNICAL DATA SHEET
v062015

XTM 15W40

DESCRIPTION

Mineral engine oil for passenger cars and delivery vans. Ideal for multi-fleet applications. Compatible with petrol, diesel and LPG cars, turbo-charged or not and equipped or not with a catalytic converter.

APPLICATION

Bardahl XTM 15w40 can be used all year long. It offers excellent cleaning properties and a very good protection against wear.

SPECIFICATIONS

This product offers the following performance level:

ACEA	A2 A3 (98) B3 E2
API	SJ/ CG-4/ CF-4/CF
VW	501.00 / 505.00
MB	229.1/ 228.1
VOLVO	VDS
MACK	EO/L
MAN	271

PROPERTIES

- ✓ Avoids deposits on pistons.
- ✓ Provides excellent cleaning properties.

SADAPS BARD AHL ADDITIVES & LUBRICANTS

ZI Tournai Ouest - 3, Rue du Mont des Carliers - B-7522 TOURNAI
Tél. : +32 69 590 360 - Fax : +32 69 590 361 - www.bardahlfrance.com



XTM 15W40

TECHNICAL DATA

Density at 20 °C	Kg/l	0,877
Viscosity at -20 °C	cP	<7000
Viscosity at 40 °C	mm ² /s	103
Viscosity at 100 °C	mm ² /s	14,1
Viscosity Index		139
Flash point COC, °C	°C	208
Pour point, °C	°C	-27
Sulphated ash contents	%	1,10

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36261	12 x 1 L
36263	3 x 5 L
36268	20 L
36264	60 L
36267	205 L

SADAPS BARDAHL ADDITIVES & LUBRICANTS