



# XTS 5W20

## DESCRIPTION

Fully synthetic engine oil formulated with last generation performance additives to reduce friction, eliminate sludge and optimize fuel consumption. Offers a good general protection of the engine.

## APPLICATION

Bardahl XTS 5w20 has been specially formulated for the lubrication of FORD EcoBoost petrol engines.

## SPECIFICATIONS

This product offers the following performance level:

ACEA	A1/B1-12
API	SN
FORD	WSS-M2C948-B

## PROPERTIES

- ✓ Avoids fuel over-consumption.
- ✓ Offers a stable viscosity and a high Viscosity Index.
- ✓ Offers excellent dispersion and detergency properties.
- ✓ Makes cold start easier.
- ✓ Provides an excellent resistance against « shearing ».
- ✓ Contains anti-corrosion, anti-wear and anti-foam additives.

### SADAPS BARD AHL ADDITIVES & LUBRICANTS



**XTS 5W20**

**TECHNICAL DATA**

Density at à 15 °C	Kg/l	0,851
Viscosity at -35 °C	mPa.s	4160
Viscosity at 40 °C	mm2/s	42,6
Viscosity at 100 °C	mm2/s	7,85
Viscosity Index		157
Flash point COC, °C	°C	218
Pour point, °C	°C	-36
TBN Alcalinity	mgKOH/g	7,7
Sulphated Ash contents	%	0,78

**RECOMMENDATIONS**

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

**REFERENCES & AVAILABILITIES**

36291	12 X 1 L
36297	205 L

**SADAPS BARD AHL ADDITIVES & LUBRICANTS**