



XTS 5W30

DESCRIPTION

Fully synthetic engine oil formulated with last generation performance additives to reduce friction, eliminate sludge and optimize fuel consumption. Offers a good general protection of the engine.

APPLICATION

Bardahl XTS 5w30 has been specially formulated to lubricate petrol and diesel engines, equipped or not with a turbo, of passenger cars and delivery vans. It is particularly suitable for modern FORD engines but also meets the requirements of the former M2C 913-A, B and C specification levels.

SPECIFICATIONS

This product offers the following performance level:

ACEA	A1/B1-12, A5/B5-12
API	SL/CF
FORD	WSS-M2C 913-D (A,B,C)
RENAULT	RN0700
JAGUAR - LAND ROVER	STJR.03.5003

PROPERTIES

- ✓ Avoids fuel over-consumption.
- ✓ Offers a stable viscosity and a high Viscosity Index.
- ✓ Provides an excellent resistance against « shearing ».
- ✓ Is highly resistant against oxidation.
- ✓ Offers excellent dispersion and detergency properties.
- ✓ Forms a lubricating film at high temperature.
- ✓ Makes cold start easier.
- ✓ Contains strong anti-corrosion, anti-wear and anti-foam additives.

SADAPS BARD AHL ADDITIVES & LUBRICANTS



XTS 5W30

TECHNICAL DATA

Density at 15 °C	Kg/l	0,853
Viscosity at -35 °C	mPa.s	4200
Viscosity at 40 °C	mm ² /s	53,30
Viscosity at 100 °C	mm ² /s	9,66
Viscosity Index		168
Flash point COC, °C	°C	220
Pour point, °C	°C	-45
TBN Alcalinity	mgKOH/g	10,1
Sulphated Ash contents	%	1,09

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36541	12 x 1 L
36543	3 x 5 L

SADAPS BARD AHL ADDITIVES & LUBRICANTS