



Eco-VG 0W-30

Fully Synthetic

Recommended by Comma for applications requiring:

VW 504 00, VW 507 00; Porsche C30;
ACEA C3

Product Features:

- Fully synthetic engine oil exceeding 5W-30 VW 504/507 fuel efficiency requirements by over 25%.
- Designed to contain low SAPS for enhanced CAT and DPF protection.
- To ensure correct oil selection use Comma's latest application guide instore or online at www.CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:

Density @ 20°C	0.840 g/cm ³
Viscosity @ 100°C	12.1 cSt
Viscosity @ 40°C	61 cSt
Viscosity Index	200
Viscosity CCS @ -35°C	5900 cP
T.B.N.	8.2 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.17%
Phosphorus	0.08%
Colour	Amber
Flash Point	>200°C
Pour Point	-48°C

UPDATED: 15-11-2018