



# eni i-Sint professional 5W-40

**eni i-Sint professional 5W-40** is a synthetic technology engine lubricant of high performances designed to lubricate passenger cars and light vans powered with either gasoline or diesel engines.

## CHARACTERISTICS (TYPICAL FIGURES)

SAE Grade		5W-40
Density at 15 °C	kg/m <sup>3</sup>	860
Viscosity at 100 °C	mm <sup>2</sup> /s	13.8
Viscosity at 40 °C	mm <sup>2</sup> /s	84
Viscosity at -30 °C	mPa·s	6300
Viscosity Index	-	170
Flash Point	°C	240
Pour Point	°C	-33

## PROPERTIES AND PERFORMANCE

- The high fluidity of **eni i-Sint professional 5W-40** ensures the best overall engine lubrication in most operating conditions, reducing friction and actively contributing to fuel economy with a simultaneous reduction of carbon dioxide (CO<sub>2</sub>) emissions.
- The presence in formulation of low volatility components reduces oil consumption.
- **eni i-Sint professional 5W-40** has outstanding detergent and dispersant properties that minimizes the formation deposits on engine components.
- **eni i-Sint professional 5W-40** strongly resists to oxidation due to high temperatures in presence of air and other agents.
- **eni i-Sint professional 5W-40** ensures, due to its extremely high fluidity, excellent cold start, guaranteeing the best lubrication of engine components during start-up phases at low temperatures, reducing wear phenomena.

## INTERNATIONAL SPECIFICATIONS

- ACEA A3/B4-10
- API SL/CF

## APPROVALS

- MB 229.1
- VW 501 01, 505 00 quality