

Product information

megol Special Engine Oil SAE 0W-20



Description

Modern high-performance motor oil. Thanks to selected HC base oils and perfectly tailored additives, particularly suitable for gasoline engines for the Asian and American markets. Keeps the engine clean, offers high shear stability and minimizes wear. Ensures quick oil penetration as well as smooth engine running under all operating conditions and is therefore very well suited to the high demands of modern engines.

Note the manufacturer's instructions!

Specifications / Approvals

API SQ • ILSAC GF-7A

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Chrysler MS-6395 • Fiat 9.55535-CR1 • Ford WSS-M2C 947-A • Ford WSS-M2C 947-B1 • Ford WSS-M2C 962-A1 • GM 6094 M • GM dexos1 Gen 3 • Honda • Mazda • Mitsubishi Dia Queen • Nissan • Toyota

Characteristic data

SAE class (engine oils)	0W-20 SAE J 300
Density at 15 °C	0,845 g/cm ³ DIN 51757
Viscosity at 40 °C	44,0 mm ² /s ASTM D7042
Viscosity at 100 °C	8,5 mm ² /s ASTM D7042
Viscosity at -40 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -35 °C (CCS)	≤ 6200 mPas ASTM D5293
Viscosity index	175 DIN ISO 2909
HTHS at 150°C	≥ 2,6 mPas ASTM D5481
Pour point	-42 °C DIN ISO 3016
Evaporation loss (Noack)	12,5 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	8,5 mg KOH/g DIN ISO 3771
Sulfate ash	0,9 g/100g DIN 51575

Characteristic data

Color number (ASTM)	L 3,5 DIN ISO 2049
---------------------	-----------------------

Available pack sizes

1 l Canister plastic	7078 AR-DE-EN-ES-FR-IT-PT-RO-RU
5 l Canister plastic	6851 AR-DE-EN-ES-FR-IT-PT-RO-RU
20 l Canister plastic	33043 DE-EN
200 l Black plate barrel	33044 DE-EN
1 l Bulk goods	33089 DE

