

Product information

megol Motorenoel Super Leichtlauf SAE 5W-40 (vollsynthetisch)



Description

Modern, fully synthetic low-friction motor oil for year-round use. Guaranteed low viscosity and high shear stability thanks to synthetic base oils and innovative additive technology. This product reliably prevents the formation of deposits, reduces frictional losses in the engine and optimally protects against wear. This results in fuel savings and extended service life of the engine. Recommended for gasoline and diesel engines (without diesel particulate filter), including those with turbochargers and catalytic converters.

Note the manufacturer's instructions!

Specifications / Approvals

ACEA A3 • ACEA B4 • API SN • API CF

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

BMW Longlife-98 • Fiat 9.55535-H2 • Fiat 9.55535-M2
• MB 229.3 • Opel GM-LL-B-025 • Porsche A40 • VW
502 00 • VW 505 00

Characteristic data

SAE class (engine oils)	5W-40 SAE J300
Density at 15 °C	0,850 g/cm ³ DIN 51757
Viscosity at 40 °C	94,0 mm ² /s ASTM D7042
Viscosity at 100 °C	14,8 mm ² /s ASTM D7042
Viscosity at -35 °C (MRV)	≤ 60000 mPas ASTM D4684
Viscosity at -30 °C (CCS)	≤ 6600 mPas ASTM D5293
Viscosity index	170 DIN ISO 2909
HTHS at 150°C	≥ 3,7 mPas ASTM D5481
Pour point	-48 °C DIN ISO 3016
Evaporation loss (Noack)	7.0 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	10,5 mg KOH/g DIN ISO 3771

Characteristic data

Sulfate ash	1,0 - 1,6 g/100g DIN 51575
Color number (ASTM)	L3,0 DIN ISO 2049

Available pack sizes

1 l Canister plastic	4808 D-GB-F-ARAB-RUS-RO-I-E-P
4 l Canister plastic	4355 D-GB-F-ARAB-RUS-RO-I-E-P
5 l Canister plastic	4809 D-GB-F-ARAB-RUS-RO-I-E-P
20 l Canister plastic	4810 D-GB