



Mobil Super™ 3000 X1 Formula FE 5W-30

Premium Full Synthetic Passenger Vehicle Motor Oil

Product Description

Mobil Super™ 3000 X1 Formula FE 5W-30 is a full synthetic motor oil that provides long engine life for many types & ages of vehicles with enhanced protection over a wide temperature range.

Features and Benefits

Mobil Super 3000 products are industry proven so you can trust you will get the performance you want from your vehicle. Mobil Super 3000 X1 Formula FE 5W-30 provides:

- Enhanced high temperature protection
- Enhanced cold start-up performance
- Enhanced engine cleanliness and sludge prevention
- Enhanced wear protection
- Helps in achieving fuel economy (as per ACEA A5/B5)

Applications

Mobil Super 3000 products are formulated to give you confidence of protection beyond that of conventional or semi-synthetic oils. ExxonMobil recommends Mobil Super 3000 X1 Formula FE 5W-30 if you regularly experience demanding conditions where it can help combat the damage caused by frequent high engine stress. Mobil Super 3000 X1 Formula FE 5W-30 can be used in a variety of gasoline and diesel automobiles, light trucks and vans designed for use of a low viscosity (HTHS) motor oil.

Mobil Super 3000 X1 Formula FE 5W-30 is intended primarily to meet the requirements of Ford but is also suitable for use in other vehicles where the viscosity and quality claims are appropriate.

Mobil Super 3000 X1 Formula FE 5W-30 can be used in all engines requiring WSS-M2C913-D and can still be used wherever WSS-M2C913-C is recommended.

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

Mobil Super 3000 X1 Formula FE 5W-30 meets or exceeds the requirements of:

ACEA A5/B5	X
API SL	X
Ford WSS-M2C913-C	X
Ford WSS-M2C913-D	X

Mobil Super™ 3000 X1 Formula FE 5W-30 has the following builder approval:

Jaguar Land Rover STJLR.03.5003	X
---------------------------------	---

Mobil Super 3000 X1 Formula FE 5W-30 is recommended by ExxonMobil for use in applications requiring:

API CF	X
--------	---

Typical Properties

Mobil Super 3000 X1 Formula FE

Viscosity	5W-30
cSt @ 40°C	53
cSt @ 100°C	9.8
Sulfated Ash, wt%, ASTM D 874	0.8
Phosphorous	0.05
Flash Point, °C, ASTM D 92	192
Density @ 15°C kg/l, ASTM D 4052	0.85
Pour Point, °C, ASTM D 97	-39

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

12-2015

Esso Petroleum Company limited
ExxonMobil House, Ermyn Way, Leatherhead, Surrey KT22 8UX

44 (0)1372 222000
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Copyright © 2001-2016 Exxon Mobil Corporation. All rights reserved.