

Mobil Vactra Oil Numbered Series

Way and Slide Lubricants

Product Description

The Mobil Vactra Oil Numbered Series are premium-quality slideway lubricants specifically designed to meet the requirements for accuracy, aqueous coolant separability, and equipment protection of precision machine tools.

The Mobil Vactra Oil Numbered Series is carefully formulated from high-quality base stocks and performance balanced with an advanced additive system that provides controlled frictional properties, compatibility with aqueous metal working fluids and corrosion protection of parts and equipment. The unique additive package provides exceptional frictional properties on a wide variety of way materials, including steel on steel and steel on polymer, reducing stick-slip and chatter. This allows smooth, uniform motion at design travel speeds enhancing machine productivity and accuracy helping to prolong tool life and enhance surface finish. The Mobil Vactra Oil Numbered Series has been optimized to provide separability from many aqueous coolants while minimizing the corrosive effects of high pH coolants on lubricated surfaces.

Features and Benefits

The Mobil Vactra Oil Numbered Series has been developed and specifically designed to provide an extra margin of machinery protection by satisfying the stringent demands of slide ways. The oils exhibit excellent lubricity and load-carrying performance contributing significantly to improving the production of quality parts. The Mobil Vactra Oil Numbered Series provides separability from many water and aqueous coolants reducing the potential negative effects of cross contamination which helps to enhance the service life and performance of both the lubricant and coolant.

Advantages and Potential Benefits

Features	Advantages and Potential Benefits
Controlled Frictional Characteristics	Helps eliminate stick-slip; allows consistently accurate machining
Multi-material Capabilities	Suitable for a wide range of way material combinations allowing for product consolidation
Water and Aqueous Coolant Separability	Helps improve the life and performance of many aqueous coolants
Adhesiveness	Prevents removal of lubricant from critical surfaces
Long Term Rust and Corrosion Protection	Helps reduce the deterioration of sliding surfaces in the presence of water and aqueous coolants



Applications

Mobil Vactra Oil Numbered Series products are recommended for the lubrication of machine tool slideway systems. They are designed for use with combinations of cast iron, steel and non-metallic way materials. Mobil Vactra Oil Numbered Series may be applied by hand, forced-feed lubricator or in flood application by circulation system.

Mobil Vactra Oil No. 1 and No. 2 are recommended for horizontal slideways on small to medium size machine tools. They are also suitable for circulating application in large machines and as a moderate duty hydraulic fluid

- Mobil Vactra Oil No. 3 and No. 4 are normally recommended for large machines where way pressures are high and good precision is required. They are also recommended for vertical and inclined slideways where drain-down can be a problem and for moderate service machine tool gear drive mechanisms.
- Mobil Vactra Oil Numbered Series can be used for lubrication of ball screws, linear guides, headstocks, translating screws
- Mobil Vactra Oil Numbered Series is recommended for applications where oil contamination of the aqueous coolants shortens coolant batch life

Specifications and Approvals

Mobil Vactra Oil Numbered Series meets or exceeds the requirements of:	Vactra Oil No 1	Vactra Oil No 2	Vactra Oil No 3	Vactra Oil No 4
Cincinnati Machine P53	X			
Cincinnati Machine P47		X		
Cincinnati Machine P50				X

Typical Properties

Mobil Vactra Oil Numbered Series:	No. 1	No. 2	No. 3	No. 4
ISO Viscosity Grade	32	68	150	220
cSt @ 40 C, ASTM D445	32	68	156	221
Flash Point, ASTM D92,	216	228	248	240
Pour Point, ASTM D97, C	-30	-33	-6	-3
Copper Strip Corrosion, ASTM D130C, 3 h	1B	1B	1B	1B
Rust Protection, ASTM D 665B	Pass	Pass	Pass	Pass
FZG Load Support, ISO 14635, Fail Stage	13	13	13	13

Due to continual product research and development, the information contained herein is subject to changes without notification. Additional important health and safety information on this product can be found in the Material Safety Data Sheet which is available at www.imperialoil.ca or by contacting the Imperial Oil Technical Help Desk at: 1-800-268-3183.

Precautions

The products described on this data sheet are manufactured from high quality petroleum base stocks, carefully blended with selected additives. As with all petroleum products, good personal hygiene and careful handling should always be practiced. Avoid prolonged contact to skin, splashing into the eyes, ingestion or vapour inhalation. Please refer to the Material Safety Data Sheet for further information.

Note: The products described on this data sheet are NOT controlled under Canadian WHMIS legislation.

Mobil Vactra Oil Numbered Series is a trademark of ExxonMobil Corporation, or one of its subsidiaries. Imperial Oil, Licensee.

12-2010