



WORLDWIDE PARTNER
OF THE AUTOMOTIVE INDUSTRY



PRO-TEC Radiator Oil Cleaner

2-component system



Product properties

Radiator Oil Cleaner reliably cleans the entire cooling system and durably removes oily deposits caused by defect cylinder head gaskets or leaking radiators. Other operationally caused contamination, e.g. coolant sludge, lime, scale will be dissolved and removed as well. Due to high quality lubrication agents, all metal and rubber parts are protected during the cleaning process. Valves, thermostats and water pumps return to their optimal performance, thus optimising operating safety and increasing the lifespan of the cooling system.



Application fields

Cooling system cleaning for all closed water-cooled systems. Also suitable for heat exchangers. Mixable with all kinds of coolants.



Application

Add the product to the cooling system before exchanging the coolant. Open the heating valve. Let the engine run for approx. 15 minutes at midrange speed and drain the fluid afterwards. Please remove all expansion tanks which are not part of the coolant circle and clean them manually. Afterwards rinse the entire cooling system thoroughly with clear water. Finally please carry out the exchange of the coolant in accordance to the manufacturer's instructions.

Sensitive to frost: **yes**



Consumption

Radiator Oil Cleaner (K1+K2) sufficient to treat cooling systems of 5 to 10 litres capacity. For lower or higher filling quantities, decrease or increase the product's application amount by 50 ml per 1 litre coolant.



Reaction time

approx. 15 minutes



Available container sizes

	Radiator Oil Cleaner		Other packaging on request
	Component 1	Component 2	
	188 ml	188 ml	
Art.-No..	P1511-1	P1511-1	

Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise.