



RAVENOL CVTF NS3/J4 Fluid

Kategorie: Gear oil for automatic transmissions

Artikelnummer: 1211132

Oil type: Synthetic

Recommendation: 999MP-NS300P, ATF J4, ATF NS-3, Mitsubishi MZ102658, Mitsubishi MZ320261, Mitsubishi MZ320262, Mitsubishi MZ320288, Nissan KLE53-00002, Nissan KLE53-00004, Suzuki CVT Fluid Green-2 99000-22B24-046, Suzuki CVT Fluid Green-2 990N0-22B24-004

Application: Passenger car



RAVENOL CVTF NS3/J4 Fluid is a synthetic CVTF (Continuously Variable Transmission Fluid), designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the CVT transmission.

RAVENOL CVTF NS3/J4 Fluid is a CVTF of the latest generation. It is especially developed for the CVT transmission of JATCO. It guarantees in any mode for maximum wear protection.

RAVENOL CVTF NS3/J4 Fluid is green colored.

1L | 1211132-001

4L | 1211132-004

10L | 1211132-010

20L | 1211132-020

20L | 1211132-B20

60L | 1211132-060

208L | 1211132-D28

Application Note

RAVENOL CVTF NS3/J4 Fluid is suitable for use in CVT transmission of following vehicles:

Nissan Qashqai J11 2013-, Nissan Pathfinder R52 2013-, Nissan Altima L33 2013-, Nissan Teana L33 2013-, Nissan Sylphe B17 2012-, Nissan Tiida C12 2014-, Nissan X-Trail T32 2013-, Nissan Elgrand E52 2013-, Nissan Murano Z51 2013-, Nissan Murano Z52 2015-, Mitsubishi Outlander GF7W/8W 2012-, Mitsubishi Delica D5 2012-, Mitsubishi Lancer 2012-, Mitsubishi ASX 2014-, Renault Koleos 2014-, Samsung QM5 2013-, Peugeot 4008 2014-, Citroen C4 Aircross 2014- and others with CVT-transmission JATCO JF016E or JF017E.

Maintenance-filling under normal operating conditions.

Characteristics

- Very good lubricating ability even at low temperatures in winter
- A high, stable viscosity index
- Very good oxidation stability
- Protection against corrosion and foam formation
- Good balanced coefficient of friction
- A high thermal and oxidative stability
- An excellent cooling capacity

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	836,0	EN ISO 12185
Colour		grün	VISUELL
Pourpoint	°C	-57	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

RAVENOL special transmission fluids are special developments for special gears and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data. Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the product information. If you are unsure about the right transmission fluid, ask your workshop or dealership for advice on the transmission type and OEM original number or ask our experts, making sure to state the VIN code (vehicle identification number) of your vehicle. Misapplication of RAVENOL special transmission fluid can lead to malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. and cause the failure of the transmission. Ravensberger Schmierstoffvertrieb GmbH is not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.

Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.

26.11.2022