

TECHNICAL CHARACTERISTICS

SELENIA 20K FOR ALFA ROMEO

PRODUCT CODE: 1640

APPLICATION

Synthetic based lubricant designed to give maximum protection on today's advanced Alfa Romeo petrol engines.

SPECIFICATIONS

SAE 10W-40, ACEA A3, API SL/CF, FIAT 9.55535-G2 APPROVAL N°F405.A05, VW 500.00 - 505.00, CCMC G5

TEST DESCRIPTION

| TEST DESCRIPTION | METHOD | UNIT | TYPICAL VALUE |
|-----------------------|-------------|-------------------|---------------|
| APPEARANCE | -- | -- | B. & C. |
| DENSITY 15°C | ASTM D 4052 | g/cm ³ | 0,872 |
| VISCOSITY @ 100°C | ASTM D 445 | cSt | 14,9 |
| VISCOSITY INDEX | ASTM D 2270 | -- | 150 |
| FLASH POINT CI. O. C. | ASTM D 92 | °C | 220 |
| T.B.N. | ASTM D 2896 | mg KOH/g | 7,2 |
| POUR POINT | ASTM D 97 | °C | <-27 |
| FOAM @ 24°C | ASTM D 892 | cc/s | TRACCES/0 |

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT

01/2014