


FLUIDE LDS



SYNTHETIC HYDRAULIC FLUID

USES

Synthetic fluid of **orange** colour for the hydraulic system of Citroën cars equipped with " **HYDRActive 3** ".

Do not use when a mineral fluid of **fluo green** colour is requested (LHM Plus).

PROPERTIES

- Super multigrade fluid.
- Exceptionally high viscosity index.
- Very low pour point.
- Very high thermal stability.
- Very good protection against wear and corrosion.
- Excellent lubricating properties.
- Contributes to improve comfort.

CHARACTERISTICS

FLUIDE LDS	Units	Typical values
Volumetric mass at 15°C	kg/m ³	820
Viscosity at - 40°C	mm ² /s	1 050
Viscosity at 40°C	mm ² /s	18
Viscosity at 100°C	mm ² /s	5.9
Viscosity index	-	320
Flash point Cleveland	°C	157
Pour point	°C	-51

The typical characteristics mentioned represent mean values.

SPECIFICATIONS

PSA S71 2710

Caution
This fluid has to be used
with a very high stress on
cleanliness



TOTAL LUBRIFIANTS
16, rue de la République
92800 PUTEAUX

Fluide LDS
November 2003



This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute a special hazard
A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.