



TOTAL QUARTZ 9000 FUTURE NFC 5W-30

Engine oil

KEY DATA

LIGHT VEHICLE RANGE



PETROL & DIESEL ENGINE OIL

SAE 5W-30

SYNTHETIC TECHNOLOGY

FUEL ECONOMY

INTERNATIONAL STANDARDS

- ✓ ACEA A5/B5 & A1/B1
- ✓ API SL/CF

MANUFACTURER APPROVALS

- ✓ Ford WSS-M2C-913C (Backward compatible with FORD WSS-M2C-913B)
- ✓ Satisfies technical requirements of FORD WSS-M2C-913D
- ✓ Satisfies technical requirements of VOLVO

APPLICATIONS

TOTAL QUARTZ 9000 FUTURE NFC 5W-30 is a synthetic technology engine oil that has been developed to cover the most stringent requirements of both gasoline and diesel engines. TOTAL QUARTZ 9000 FUTURE NFC 5W-30 is particularly suited to turbocharged, multi-valve and direct injection engines.

This engine oil can be used in the most difficult operating conditions (motorways, dense city traffic...), and for all weather. TOTAL QUARTZ 9000 FUTURE NFC 5W-30 is perfectly adapted to all FORD vehicles equipped with catalyts

CUSTOMER BENEFITS

- **Reduced environmental impact: 3% reduction in fuel consumption**, as measured by the official ACEA test: M111FE.
- **Protection for pollution-control systems:** With its low phosphorus content, this lubricant also optimises the way in which three-way catalytic converters operate, preventing them from getting damaged through poisoning. This reduces NOx, HC and CO in particular.
- **Engine protection and cleanliness:** This oil contains detergent and dispersive additives and offers the best possible protection in its category against wear and deposits.
- **Easier cold starts:** Easy cold starts due to its extreme fluidity at low temperature.

Oil change intervals: To be modified based on the usage, please always refer to the car owner's manual.

CHARACTERISTICS*

| Test | Unit | Test method | Result |
|------------------------------|--------------------|-------------|--------|
| Viscosity grade | - | SAE J300 | 5W-30 |
| Density at 15°C | kg/m ³ | ASTM D1298 | 0.851 |
| Kinematic viscosity at 40°C | mm ² /s | ASTM D445 | 54 |
| Kinematic viscosity at 100°C | mm ² /s | ASTM D445 | 9.8 |
| Pour point | °C | ASTM D97 | -36 |

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet. This can be obtained on request from your local reseller and is available for consultation at www.quickfds.fr.

This product should not be used for any purposes other than the ones for which it is intended.

When disposing of the product after use, please protect the environment and comply with local regulations.